





G-2RB

Performance curve for Vacuum pump



2RB 430


Performance curve for Compressor



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of +/- 10 %.
The total pressure differences are valid for suction and ambient temperatures up to 25 °C.
For other conditions please confer with us.

Each G-2RB type can be applied both as vacuum pump and compressor in continuous operation over the total stated performance curve range. The motors are available as standard for the input voltage range of 50 and 60 Hz and for protection category IP 55 as well as approved for UL and CSA.

2RB430 Dimensions



Type	Phases																									X-Borungen		
		A	B	C	D	E	F	G	H	J	K	L	M	N	0	P	Q	ØR	S	U	V ₁₋₃	V _{II-3}	V _{III-3}	V _{IV-3}	YxZ	X-Holes	Ø	
2RB 430-7AA 11	1 ~	286	302	115	225	255	311	160	154	120	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	M16x1.5	M25x1.5	-	-	M6x15	0°/120°/240°	174	
2RB 430-7AA21	1 ~	286	302	115	225	255	311	160	154	120	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	M16x1.5	M25x1.5	-	-	M6x15	0°/120°/240°	174	
2RB 430-7AH06	3 ~	286	302	115	225	255	288	135	154	111	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	-	-	M25x1.5	M16x1.5	M6x15	0°/120°/240°	174	
2RB 430-7AH16	3 ~	286	302	115	225	255	311	160	154	120	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	-	-	M25x1.5	M16x1.5	M6x15	0°/120°/240°	174	
2RB 430-7AH26	3 ~	286	302	115	225	255	311	160	154	120	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	-	-	M25x1.5	M16x1.5	M6x15	0°/120°/240°	174	
2RB 430-7AV25	1 ~	286	302	115	225	255	311	160	154	120	95	130	70	75	46	G1¼(15tief-deep)	72	12	3	M6x19	M16x1.5	M25x1.5	-	-	M6x15	0°/120°/240°	174	



Selection and ordering data

Type 2RB430

Curve No.	Order No.	Fre- quency	Rated power	Input voltage	Input current	Permissible total differential pressure ²⁾		Sound pressure level ³⁾	Weight ca.
		Hz	kW	V	A	Vacuum mbar	Compressor mbar	dB(A)	kg

3~ 50/60 Hz IP55 isolation material class F 1)

A 210	2RB430-7AH06	50	0.7	200D ... 240D	345Y...415Y	3.8D	2.2Y	-75	75	64	14
A 211	2RB430-7AH06	60	0.83	220D ... 275D	380Y...480Y	3.8D	2.2Y	-50	50	65	14
A 212	2RB430-7AH16	50	0.85	200D ... 240D	345Y...415Y	4.2D	2.4Y	-120	120	64	17
A 213	2RB430-7AH16	60	0.95	220D ... 275D	380Y...480Y	4.0D	2.3Y	-90	70	65	17
A 214	2RB430-7AH26	60	1.3	200D ... 240D	345Y...415Y	6.6D	3.8Y	-170	210	64	18
A 215	2RB430-7AH26	60	1.5	220D ... 275D	380Y...480Y	6.9D	4.0Y	-200	160	65	18


1~ 50/60 Hz IP55 with attached condenser for continuous operation

A 210s	2RB430-7AA11	50	0.8	230		5.2		-100	110	64	16
A 211s	2RB430-7AA11	60	0.9	230		5.8		-100	110	66	16
A 212s	2RB430-7AA21	50	1.1	230		7.3		-170	210	64	17
A 213s	2RB430-7AA21	60	1.3	230		8.3		-145	145	66	17
A 214s	2RB430-7AV25	50	1.1	115	230	14.6	7.3	-170	210	64	16
A 215s	2RB430-7AV25	60	1.3	115	230	16.6	8.3	-145	145	65	16

Other voltage ranges

		☐ ☐	
50Hz	60Hz	 	
3~			
185...225 V D/320...390 V Y	200...240 V D/345...415 V Y	H 1	
200...240 V D/345...415 V Y	200...275 V D/380...480 V Y	H 6	
345...415 V D	380...480 V D	H 7	
500 V D	575VD	C 5	
Machines according to the ATEX norm 94/4 EG are available for the whole performance range.			
Following types available: Category 3 G, 3/2 G, 3 D and 3/2 D.			
1~			
100 / 200 V	100 / 200 V	V 4	
115 / 230 V	115 / 230 V	V 5	
230V	230V	A 1	

Further voltage range on request; please quote in plain text.



All G-2RB achieve the standards and norms of the low voltage directive (LVD)2006/95/EC, rotating electrotechnical motor EN 60034-1-2004, electromagnetic compatibility(EMC)EN55014-1/2,EN61000-2/-3/-4/-6.

- 1) For standard UL for ELECTRIC MOTOR UL 1004-1.
- 2) Relief-valve are available for limiting differential pressure.
- 3) Measuring-surface sound-pressure level acc. to DIN EN 21680, measured at a distance of 1 m. The pump is throttled to an average suction pressure, a hose is connected to the discharge side (compressor) / suction side (vacuum pump), but is not fitted with relief valves.

The motors are designed according to the DIN EN 60 034 / DIN IEC 34-1 and temperature class F.

For the three phase machines the tolerances are +/- 10 % for fixed voltage and +/- 5 % for voltage range.

The single phase machines are designed with a +/- 5 % tolerances. If only 90 % of the maximum allowed pressure will be used for the continuous operating then the allowed voltage range add to +/- 10 %.

For all single and three phase machines which designed according to the UL and CSA norm (UL 1004-1) the maximum allowed voltage tolerances are - 10 % resp. + 6 %.

The frequency tolerance is maximum +/- 2 %.

Changes in particular the quoted performance curve, datas and weights without prior notice. The figures are without obligations.

ZHEJIANG GREENCO INDUSTRY CO.,LTD

Add:danya industrial zone.zeguo.wenling zhejiang China

P.C:317523

Tel:0086-576-86428999

Fax:0086-576-86409555

E-mail:greenco@greenco.cn

Http://www.greenco.cn