


## 2RB 713-1HY99 Ordering data

## 2RB 713-1HY99



The performance curves are valid for pumping air at 15°C at the inlet flanges with an air pressure of 1.013mbar and a tolerance of  $\pm 10\%$ . The total pressure differences are valid up to an intake and ambient temperature of 25°C.

| No | Rated Speed | Rated power | Maximim Air flow  | Maximim vacuum | Maximim pressure | Sound-level | Weight approx | Vacuum relief       |
|----|-------------|-------------|-------------------|----------------|------------------|-------------|---------------|---------------------|
| 编号 | 转速          | 配置功率        | 最大流量              | 最大真空           | 最大压力             | 噪音          | 重量            | Items x type        |
|    | RPM         | KW          | m <sup>3</sup> /h | mbar           | mbar             | dB(A)       | Kg            | 2BX                 |
| 1  | 3000        | 2.2         | 320               | -190           | 190              | 69          | 16            | 1 x ...2110/...2145 |
|    | 3600        | 2.55        | 380               | -190           | 190              | 72          |               |                     |
|    | 4200        | 3.0         | 440               | -160           | 160              | 75          |               |                     |
|    | 5000        | 3.8         | 530               | -130           | 130              | 80          |               |                     |
| 2  | 3000        | 3.0         | 320               | -260           | 270              | 64          |               |                     |
|    | 3600        | 3.45        | 380               | -240           | 230              | 70          |               |                     |
|    | 4200        | 4.3         | 440               | -270           | 220              | 72          |               |                     |
|    | 5000        | 5.0         | 530               | -220           | 210              | 75          |               |                     |
| 3  | 3000        | 4.0         | 320               | -290           | 360              | 64          |               |                     |
|    | 3600        | 4.6         | 380               | -320           | 310              | 70          |               |                     |
|    | 4200        | 6.0         | 440               | -340           | 300              | 72          |               |                     |
|    | 5000        | 6.9         | 530               | -300           | 270              | 75          |               |                     |

